

Receipt Printer

Standard features

- Direct-thermal receipt printing
- Looping presenter with pull detector
- Retract & retain function
- Full-width or partial guillotine
- Auto media loading
- Horizontal or vertical mounting
- Various media options for media-roll mounting behind and below
- USB or parallel IEEE 1284 or RS-232 serial connectivity
- Windows® drivers for plug-and-play and direct addressing with ESC commands

Applications include:

- Access and administration
- Parking applications
- Event ticketing
- Receipts, coupons and statements
- Information delivery
- Promotional coupons/vouchers
- Loyalty vouchers
- Vending-machine receipts
- Photo kiosks
- Currency exchange
- Recycling machine receipts
- Fuel pumps
- Gaming/lottery



Receipt Printer : Spec

Resolution

- 8 dots per mm (203dpi)

Maximum print area

- Width: 72mm (2.8")
- Length: 70mm (2.76") to 600mm (23.6")

Maximum print speed:

- 150mm (6") per second

Physical characteristics

- Width: 105mm (4.1")
- Height: 65mm (2.6")
- Depth: 145mm (5.7")
- Weight: 1.1kg (2.4lb)

Media specifications

- Paper widths: 58mm (2.28"), 60mm (2.36"), 80mm (3.15") and 82.5mm (3.25")
- Maximum diameter of media roll: 250mm (9.8")
- Minimum diameter of media core: 25mm (1")
- Media thickness: 0.054mm (0.002") to 0.11mm (0.004")
- Media types: Roll or fanfold paper

Environmental

- Operating temp: -10°C (14°F) to 50°C (122°F)
- Storage temp: -10°C (14°F) to 50°C (122°F)
- Operating humidity: 10% to 95% RH non-condensing
- Storage humidity: 10% to 95% RH non-condensing excluding paper

Electrical

- 24VDC +/-5%, average of 2A when printing (85mA idle)

Options and accessories

- Universal variable-position roll holder, 200mm diameter maximum
- Adaptor for using roll holder below printer, 250mm diameter maximum
- Roll holder wall mount, 150mm diameter maximum
- Quick-fit hubs and leafspring retainer
- Paper-low sensor with 300mm cable