

Protouch Payment Kiosk

- ✓ Full Payment Including Change
- ✓ 19" ELO PCAP Touchscreen
- ✓ Robust mild steel body - powder coated white
- ✓ Easy To Brand
- ✓ Anti-Vandal Kiosk

LCD Specification

LCD Display	19" TFT Active Matrix Panel
Active Area	376 (H) x 301 (V) mm
Max Resolution	1280 x 1024
Display colour	16.7M (6 bits and HI-FRC)
Contrast Ratio	1000:1
Brightness	225 nits
Response Time rise:	5ms
Display Colour	16.7M
Aspect Ratio	5:4
Viewing Angle	85°/80° or 170°/160°
Touch Technology	Projective Capacitive
Operating Temperature	0° ~ 40°C





Humidity	20% ~ 80%
Power	DC 12V, 4.16A
Power Consumption	25W
Lifetime Typical	50,000 hours

Kiosk Specification

Weight	150kg (Approx)
Dimensions	Width: 650mm
	Height: 1700mm *
	Depth: 415mm
Additional Options	<ul style="list-style-type: none"> Coin & note acceptance with recycling Coin acceptance with full change and hopper system PCI P2PE unattended chip & pin with contactless (Fully PSI DSS 3.1 Compliant) 60,80mm 112mm & A4 thermal printing Fujitsu Industrial kiosk PC 1 & 2D Barcode scanning RFID / MSR card dispensing RFID / MSR card reading Biometric reading Front, side, top & rear customer branding WIFI with anti-vandal antenna Kiosk Camera Speaker system Microphone

