



## The 17" Geode 2

The high specification 17" commercial grade touchscreen, for extremely demanding environments. Ticking all the boxes an EPoS touch screen should it is feature rich, highly reliable and comes at an unbeatable price. You'll often spot it transforming busy retail and hospitality till points into efficient, speedy, customer happy environments.

- ✓ 17" LCD 5 wire resistive touch screen
- ✓ Rock solid to touch through 90 degrees
- ✓ Stylish housing with a slim black plastic bezel
- ✓ Highly durable - Scratch resistant screen
- ✓ VESA standard versatile installation
- ✓ Innovative power saving technology display

### Detailed Specification

Panel	Cell Type / Glass Surface; TFT LCD / Black Anti-Glare, Low reflection coating Aspect Ratio / Size ; 5 : 4 / 17" viewable diagonal area Active Area / Pixel Pitch; 337.92(H) x 270.34(V) mm / 0.264(H) x 0.264(V)mm Native Resolution / Colours; 1280(H) x 1024(V) / 16.7 Million Brightness / Contrast; 300 cd/m (typ) / 800 : 1 Response Time; < 5 ms Light Source; CCFL , Long life, 50,000 hrs (typ)
Input Source	Signal; Analog RGB (0.7/1.0 V, 75 ohms) Sync; Seperate Sync, Composite Sync, Sync On Green Frequency; $f_h$ : 30 ~ 82Khz . $F_v$ : 50 - 75Hz Audio System; 2W Speaker x2
Input Terminals	1 x VGA (15 Pin Femaile D-Sub) , 1 x PC Audio (Stereo Headphone Jack) , 1 x DC Power plug





Convenient Features	Auto Calibration, Back Light Adjustment, Plug & Play (VESA DDC/CI, DDC 2B) OSD Multi-Languages , Wall Mount Ready (VESA 75 x 75 mm)
Power	External AC-to-12VDC power adapter with universal / Auto-Sensing, AC 90 to 260V, 50 / 60 H
Power consumption	Operation / Power Saving; 30 watt. < 2 watt (Support DPMS)
Operating Conditions	Temperature / Humidity; 0 c ~ 50 c (32 F ~ 122 F . 10% ~ 90 % (no condensation)
Storage Conditions	Temperature / Humidity; -20 c ~ 60 c (-4 F ~ 140 F . 10% ~ 90 % (no condensation)
Dimensions	Physical; With Base (W x H x D) : 374.5 x 363.5 x 240.9(mm)
5 Wires Resistive Touch (USB/RS232)	Resolution; 2048 x 2048
	Touch Method; Finger, gloved hand or any other pointer
	Touch Accuracy; + 2mm (for 42" screen) over 90% of the touch sensitive area
Weight	N.W. / G.W.; 5.0KGS / 5.5KGS



**Industrial Grade**



**As used by Sports Direct**

